

OUTDOOR Large Displays 1L10C and 2L10C



EZMR-1L10C-OUT
EZMRH-1L10C-OUT



EZMR-2L10C-OUT
EZMRH-2L10C-OUT



EZMT-1L10C-OUT



EZMT-2L10C-OUT

EZMarquee Specifications (OUTDOOR)

Part Number	EZMR-1L10C-OUT EZMR-1L10C-E-OUT EZMR-1L10C-D-OUT EZMR-1L10C-P-OUT EZMRH-1L10C-OUT EZMRH-1L10C-E-OUT EZMRH-1L10C-D-OUT EZMRH-1L10C-P-OUT	EZMT-1L10C-OUT EZMT-1L10C-E-OUT EZMT-1L10C-D-OUT EZMT-1L10C-P-OUT	EZMR-2L10C-OUT EZMR-2L10C-E-OUT EZMR-2L10C-D-OUT EZMR-2L10C-P-OUT EZMRH-2L10C-OUT EZMRH-2L10C-E-OUT EZMRH-2L10C-D-OUT EZMRH-2L10C-P-OUT	EZMT-2L10C-OUT EZMT-2L10C-E-OUT EZMT-2L10C-D-OUT EZMT-2L10C-P-OUT
Outdoor Model	RED LED	TRI-Color LED	RED LED	TRI-Color LED
High-bright Model	RED Sunlight Readable 8000 nits		RED Sunlight Readable 8000 nits	
Specification	1 Line of 10 Char (2")		2 Lines of 10 Char (2")	
Max. Viewable Distance	100 Feet with 2" Characters		200 Feet with 4" Characters	
Power	8 watts	14 watts	15 watts	28 watts
Approvals	UL, CUL, CE			
Enclosure	NEMA 4X			
Operating Temp.	-20° to 60° C Ambient			
Storage Temp.	-40° to 95° C Ambient			
Humidity	10% to 95% RH, Non-Condensing			
Input Power	110/220 VAC, 47-63Hz			
Electrical Interference	NEMA ICS 2-230 Showering Arc Test			
Electrical Tolerance	ANSI C37.90a-1974 (SWC) Surge With-Stand Capability Test			
Vibration	5 - 55 Hz 2G for 2 hours in the X, Y, and Z axis			
Shock	10G for under 12ms in the X, Y, and Z axis			
Serial Comm.	Port 1 RS232; Port 2 RS422/485			
External Dim.	18.9" x 4.8" x 2.8" (479.25 x 121.43 x 69.85mm)		18.9" x 6.2" x 2.8" (479.25 x 156.13 x 69.85mm)	
Weight	2.8 lbs	3 lbs	5 lbs	5.2 lbs