

UNIVERSAL Large Displays 2L20C and 2L40C



EZMR-2L20C



EZMT-2L20C



EZMR-2L40C



EZMT-2L40C

EZMarquee Specifications (UNIVERSAL)

Part Number	EZMR-2L20C EZMR-2L20C-E EZMR-2L20C-D EZMR-2L20C-P	EZMT-2L20C EZMT-2L20C-E EZMT-2L20C-D EZMT-2L20C-P	EZMR-2L40C EZMR-2L40C-E EZMR-2L40C-D EZMR-2L40C-P	EZMT-2L40C EZMT-2L40C-E EZMT-2L40C-D EZMT-2L40C-P
Displaytype	RED LED	TRI-Color LED	RED LED	TRI-Color LED
Specification	2 Line of 20 Char (2")		2 Lines of 40 Char (2")	
Max View. Distance	200 Feet with 4" Characters			
Power Consumption	30 VA	55 VA	54 VA	100 VA
Approvals	CE, UL, CUL			
Enclosure	IP 54/NEMA 12			
Operating Temp.	0° to 60° C Ambient			
Storage Temp.	-40° to 95° C Ambient			
Humidity	10% to 95%, Non-Condensing			
Input Power	90 to 230 VAC, 47-63Hz			
Electrical Interference	NEMA ICS 2-230 Showering Arc Test			
Vibration	5 - 55 Hz 2G for 2 hours in the X, Y, and Z axis			
Shock	10G for under 12ms in the X, Y, and Z axis			
Serial Communication	RS232; RS422/485			
Add. Ports (Option)	Ethernet, Devicenet, Profibus			
External Dimensions	936 x 156 x 70 mm		1831 x 144 x 70 mm	
Weight	3,6 Kg	3,8 Kg	6,8 Kg	7,2 Kg