

INTELLIGENT Large Displays 2L10C, 2L20C, 4L20C



2 Lines, 10 Characters - Tri-Color



2 Lines, 20 Characters - Tri-Color



4 Lines, 20 Characters - Tri-Color

EZ iMarquee Specifications (iNTELLIGENT)

Part Number	EZiMT-2L10C	EZiMT-2L20C	EZiMT-4L20C
LED Type	TRI-Color LED (Green, Red, Amber)		
LED Life	100,000+ Hours		
Specification	2 Line of 10 Char (2")	2 Line of 20 Char (2")	4 Lines of 20 Char (2")
Max. Viewable Distance	200 Feet with 4" Characters	200 Feet with 4" Characters	400 Feet with 8" Characters
Power	28 watts	55 watts	100 watts
Approvals	UL, CUL, CE		
Enclosure	NEMA 12 (Indoor Only)		
Operating Temp.	-20° to 60° C Ambient		
Storage Temp.	-40° to 95° C Ambient		
Humidity	10% to 95% RH, Non-Condensing		
Input Power	110/220 VAC, 47-63Hz		
Electrical Interference	NEMA ICS 2-230 Showering Arc Test		
Electrical Tolerance	ANSI C37.90a-1974 (SWC) Surge With-Stand Capability Test		
Vibration	5 - 55 Hz 2G for 2 hours in the X, Y, and Z axis		
Shock	10G for under 12ms in the X, Y, and Z axis		
Ethernet Comm.	10/100 Base T Ethernet (Master / Slave) (see complete list of protocols supported)		
Serial Comm.	Port 1 RS232; Port 2 RS422/485 (Master / Slave) (see complete list of protocols supported)		
Data Logging	USB or Micro SD Card		
External Dim.	18.9" x 6.2" x 2.8" (479.25 x 156.13 x 69.85mm)	36.225" x 5.67" x 2.769" (920.12 x 144.02 x 70.33mm)	36.577" x 11.720" x 2.750" (929.06 x 297.69 x 69.85mm)
Weight	2.8 lbs	3 lbs	5 lbs