

INTELLIGENT Large Displays 2L40C and 4L40C



2 Lines, 40 Characters - Tri-Color



4 Lines, 40 Characters - Tri-Color

EZ iMarquee Specifications (INTELLIGENT)		
Part Number	EZiMT-2L40C	EZiMT-4L40C
LED Type	TRI-Color LED (Green, Red, Amber)	
LED Life	100,000+ Hours	
Specification	2 Line of 40 Char (2")	4 Line of 40 Char (2")
Max. Viewable Distance	200 Feet with 4" Characters	400 Feet with 8" Characters
Power	100 watts	180 watts
Approvals	UL, CUL, CE	
Enclosure	NEMA 12 (Indoor Only)	
Operating Temp.	-20° to 60° C Ambient	
Storage Temp.	-40° to 95° C Ambient	
Humidity	10% to 95% RH, Non-Condensing	
Input Power	110/220 VAC, 47-63Hz	
Electrical Interference	NEMA ICS 2-230 Showering Arc Test	
Electrical Tolerance	ANSI C37.90a-1974 (SWC) Surge With-Stand Capability Test	
Vibration	5 - 55 Hz 2G for 2 hours in the X, Y, and Z axis	
Shock	10G for under 12ms in the X, Y, and Z axis	
Ethernet Comm.	10/100 Base T Ethernet (Master / Slave) (see complete list of protocols supported)	
Serial Comm.	Port 1 RS232; Port 2 RS422/485 (Master / Slave) (see complete list of protocols supported)	
Data Logging	USB or Micro SD Card	
External Dim.	72.3" x 5.67 x 2.802" (1836.29 x 144.02 x 71.16mm)	72.867" x 10.771" x 4.000" (1850.82 x 273.58 x 101.6mm)
Weight	15 lbs	30 lbs